Pipe Tracers Pinpoint Location

HMG Water Solutions are able to offer a wide range of Pipe Tracers to meet any requirements.



Plastic Pipe Tracers 20m or 50m. Flexible with a minimal bending radius and a 6mm diameter rod and tip.



Fibreglass rod tracer wires. 4.5mm diameter with no slip ring and a 5.5mm diameter with an in-built slip ring



Fibreglass rods either in 6mm or 9mm diameter, up to 200meters long without slip rings.

Features:

- From 20meters in length through to 200meters
- Tip and line tracing
- From 6mm diameter rod and tip
- With or without slip rings available
- For use with any Cable Avoidance Tool Locator and signal generator
- Optimised for 33kHz
- Up to 4meters detection



Pipe Tracers Pinpoint Location

Product Specification	Plastic Pipe Tracer	Plastic Pipe Tracer	Duct- Trace	Flexible Tracer	Duct- Trace	Duct- Trace
	6mm	6mm	4.5mm	5.5mm	6mm	9mm
20m	202120	Х	Х	Х	Х	X
30m	Х	Х	203030	Х	207030	Х
50m	Х	202150	203050	Х	207050	208050
60m	Х	X	Optional	X	207060	208060
80m	X	X	203080	202180	207080	208080
100m	X	X	X	X	207100	208100
120m	X	Х	Х	Х	207120	208120
150m	X	X	X	X	Х	208150
180m	X	X	X	X	X	208180
200m	X	X	Х	Х	Х	208200
Height* in mm	250	290	560	588	700	950
Depth* in mm	120	165	180	288	250	400
Width* in mm	150	240	410	485	580	820
Weight	1.3kg	2.1kg	4 to 6kg	7.5kg	5 to 25kg	18 to 34kg
Tip Tracing Depth	Up to 3m					
Line Tracing Depth *1	Up to 4m		Up to 3m	Up to 4m	Up to 3m	Up to 3m
Tip Dimensions mm	n/a	n/a	9x75	9.5x160	9x75	12x75
Optimum Signal	33kHz					

- X Not Available * Dimensions approximate. They may change without notice
- *1 Dependent upon locator and signal generator and site conditions
- *2 Bending radius reduces to 150mm, 50mm from the tip

