



**Water Solutions**

## Sebalog D-3 Network Network - Data Loggers

Sebalog D-3 - The most universal Data Logger

Thanks to its compact and robust design and the totally waterproof housing, the Sebalog D-3 data logger is very hard-wearing. It reliably informs you of the flow rate status from the pressure and flow measurements in your supply network on up to 4 channels. It sends the latest data automatically on a day-to-day basis via 2G or 3G to your control centre or can be received, edited and displayed within the SebaCloud or the new POSEYEDON cloud platform.

### Always up to date with the online measurement and alarm function

Great emphasis was placed on user-friendliness with the Sebalog D-3. It supports online measurements on all channels which enables you as the user to access any saved measurement data and up-to-date readings at any time from the convenience of your smartphone.

### Feel secure!

The Sebalog D-3 alarm feature can inform you immediately if there is a significant change in the pressure level or flow rate, because the current measuring data of the Sebalog D-3 are directly available online after an alarm. You have a reliable overview of your data - no matter where you are - to know exactly where the source of the noise is located.



**CONTACT OUR TEAM TODAY TO DISCUSS YOUR REQUIREMENTS**  
**01249 816181 > info@hmglocation.co.uk > www.hmglocation.co.uk**

©2021 HMG Water Solutions Ltd. All rights reserved to make changes to design and specification without prior notice or consent. E&OE

WWW.HMGLOCATION.CO.UK LOCATE : SURVEY : DETECT 01249 816181 INFO@HMGLOCATION.CO.UK





# Sealog D-3 Network Network - Data Loggers

## Water Solutions

<b>Sealog D-3</b>	
Protection Class	IP68
Temperature Range	-20°C bis +60°C
State Control	LED
Weight	900g
Dimensions	185mm x 115mm
<b>Power Supply</b>	
Internal Lithium Battery	Up to 5 years (standard configuration)
External Battery	Optional
External Power Supply via VK 76	12V 1.5A
<b>Input (max. 4)</b>	
Digital	4, frequency/pulse
Analogue	2, 0 ... 5V/0 ... 20mA
Relays Input	2
Relays Output	2
<b>Collection of Data</b>	
Internal Pressure Sensors	0 - 16 bar (standard), 25 bar, 35 bar
Recording Interval	1 sec - 24h
Memory	Up to 1.7 Mio. measurements
External Memory	SebaCloud
Alarm Messages	SMS, e-mail
<b>Communication</b>	
SebaCloud 7 FTP Server	SebaDataView-3 / SCADA / GIS
Communication	GSM / GPRS / 3G / UMTS

**CONTACT OUR TEAM TODAY TO DISCUSS YOUR REQUIREMENTS**  
**01249 816181 > [info@hmglocation.co.uk](mailto:info@hmglocation.co.uk) > [www.hmglocation.co.uk](http://www.hmglocation.co.uk)**

©2021 HMG Water Solutions Ltd. All rights reserved to make changes to design and specification without prior notice or consent. E&OE



[WWW.HMGLOCATION.CO.UK](http://WWW.HMGLOCATION.CO.UK) [INFO@HMGLOCATION.CO.UK](mailto:INFO@HMGLOCATION.CO.UK)

01249 816181

LOCATE : SURVEY : DETECT

[WWW.HMGLOCATION.CO.UK](http://WWW.HMGLOCATION.CO.UK)